

Hercules Climbers: 902-299, 902-300, 902-301, 902-302: Material Specifications

Shall be fabricated of 5" O.D. galvanized steel. All steel tubing shall be fabricated from FloCoat galvanized steel. The patented in-line triple zinc coating process provides a smooth shiny uniform appearance with up to 25% greater corrosion resistance than galvanized schedule 40 pipe along with greater strength and lighter weight for comparable sizes. Independent testing shows up to 6 times greater corrosion resistance when powder coating over bare steel. FloCoat galvanized triple-coat corrosion protection 8, 11 or 13 Gauge, powder coated, with a 50,000 PSI yield and 55,000 PSI tensile strength. Aluminum dome style top cap is factory riveted with stainless rivet. All attachments shall be direct bolt via self-tapping torx screws. All parts shall be steam cleaned with iron phosphate to provide better corrosion and adhesion and have a baked-on electrostatically applied polyester dry powder coating. All products shall be oven baked at 400 degrees Fahrenheit to ensure superior paint adhesion. We use stainless steel, vandal-resistant hardware: button head cap screws. Some climbers will feature ¾" polyethylene routed plastic climbing panels along with 16mm galvanized core rope with egg and tee connectors with 3/8" threaded rod connections. All rope shall feature 16 mm steel cable wrapped in durable nylon.