

# SportsPlay Outdoor Fitness Specifications

## Material

Outdoor Fitness equipment shall be fabricated from 12 gauge steel tubing that has been treated via Cathaphoresis, an electrochemical coating process for metallic surfaces widely used in the automotive industry owing to its penetration and long lasting life. The mounting tube shall measure 6 5/8" O.D. with a wall thickness of .16". Action arms shall measure 2 3/8" O.D. with a wall thickness of .13" and support arms shall measure 1" O.D. with a wall thickness of .12". All units shall support 300 lbs. All articulating action shall feature the patent pending "Torsion" system, which will allow for a fluid range of motion. All stationary and moving platforms shall feature a molded plastic fitting. A flat mounting plate measuring 16" X 16" with a thickness of 3/8" will secure each unit to the in-ground mounting plate. A plastic ring will cover the attachment plate and will be secured via 3/8" X 2" stainless steel button head bolt.

## Color

This product is available in Silver with Orange plastic accents

## Assembly

Each unit will include an in-ground anchor system that will require a minimum hole that is 18"W X 18"L X 18"D. If your frost line is deeper than 18", you must dig the hole to a depth that allows concrete below the frost line for your region. The hole must be flat bottomed. An estimated .125 yards of concrete per hole will be required to secure the anchor system. Once the anchor system is in place, the fitness unit will slide over the anchor and 3/4" nuts will secure the unit to the anchor. Plastic ring will cover mounting hardware.

## Warranty

SportsPlay Outdoor Fitness products are covered by a 1-year warranty from the date of purchase. This warranty will not cover acts of God or Vandalism. Improper use and failure to follow installation instructions will void this warranty.

## Maintenance

The product is virtually maintenance-free and requires only periodic cleaning with a sponge and a solution of mild detergent and water to remove surface dirt. Do not clean with solvent or petroleum base products.

